



# International Journal for Innovative Engineering and Management Research

A Peer Reviewed Open Access International Journal

[www.ijiemr.org](http://www.ijiemr.org)

**COPY RIGHT**



**ELSEVIER**  
**SSRN**

**2022 IJIEMR.** Personal use of this material is permitted. Permission from IJIEMR must be obtained for all other uses, in any current or future media, including reprinting/republishing this material for advertising or promotional purposes, creating new collective works, for resale or redistribution to servers or lists, or reuse of any copyrighted component of this work in other works. No Reprint should be done to this paper, all copy right is authenticated to Paper Authors

IJIEMR Transactions, online available on 5<sup>th</sup> Sept 2022. Link

[:http://www.ijiemr.org/downloads.php?vol=Volume-11&issue=Issue 10](http://www.ijiemr.org/downloads.php?vol=Volume-11&issue=Issue 10)

**DOI: 10.48047/IJIEMR/V11/ISSUE 10/01**

Title A Convolutional Neural Network-based Method for Identifying COVID19 Face Masks

Volume 11, ISSUE 10, Pages: 1-8

Paper Authors

**Mr.G.Venkateswarlu, S.Renuka**



USE THIS BARCODE TO ACCESS YOUR ONLINE PAPER

To Secure Your Paper As Per **UGC Guidelines** We Are Providing A Electronic Bar Code

## A Convolutional Neural Network-based Method for Identifying COVID19 Face Masks

Mr.G.Venkateswarlu<sup>1</sup>, S.Renuka<sup>2</sup>

#1 Asst.Prof , Dept of CSE,M.Tech(10 years of experience),PBR VITS, Kavali.

#2PG Schloar, Dept of MCA , PBR VITS, Kavali.

**ABSTRACT\_** Coronavirus sickness 2019 has impacted the world considerably. One significant safety approach for human beings is to put on masks in public settings. so many public provider carriers require consumers to employ the carrier just if they put on masks correctly. However, there are simply a few lookup research about face masks recognition relying purely on photo analysis. In this we offer, MobileNet Mask, it is a deep learning-based multi-phase face masks detection model for blocking human transmission of SARS-CoV-2. Two outstanding face masks datasets have been utilised to instruct and take a look at the model for detecting with and barring a face masks from the snap photographs and video stream. Experiment effects demonstrate that with 770 validation samples MobileNet Mask achieves an accuracy of ~ 93 percent and with 276 validation samples it attains an accuracy of roughly ~ 100 percent . The penalties demonstrated that our proposed technique is fairly exact.

### 1.INTRODUCTION

Coronavirus sickness 2019 has impacted the world considerably. One significant safety approach for human beings is to put on masks in public settings. so many public provider carriers require consumers to employ the carrier just if they put on masks correctly. However, there are simply a few lookup research about face masks recognition relying purely on photo analysis. In this we offer, MobileNet Mask, it is a deep learning-based multi-phase face masks detection model for blocking human transmission of SARS-CoV-2. Two outstanding face masks datasets have been utilised to instruct and take a look at the model for detecting with and barring a face masks from the snap photographs and video stream.

Experiment effects demonstrate that with 770 validation samples MobileNet Mask achieves an accuracy of ~ 93 percent and with 276 validation samples it attains an accuracy of roughly ~ 100 percent . The penalties demonstrated that our proposed technique is fairly exact have been identified as a virus. Loss of smell and taste was added as a compatible and defining symptom of this virus in a March 2020 update by the Council of State and Territorial Epidemiologists (CSTE) [3]. Moreover, various studies have indicated that the pandemic has affected us mentally, both because of the constraints to which we have been subjected in an effort to reduce the spread of SARS-CoV-2 and because of the repercussions left by the virus once the patient has recovered. Some

persons are more likely to experience difficulties with their mental health due to demographic and psychosocial characteristics that are exacerbated by the epidemic. Stress, emotional disorders, sadness, anxiety, sleeping problems, panic attacks, and other mental health issues [4]. COVID-19 symptoms and its rapid spread among humans have both been the subject of research. Studies have shown that the prevalence of disease is greater in confined spaces with poor ventilation. This is because virus particles can disperse in airborne microdroplets, often known as aerosols. Humans create these aerosols when we vocalise (sing, laugh, etc.). Furthermore, their velocity increases when the flow is stronger, such as when we run or shout. The larger drops eventually hit the ground, but the nucleus, which is where the virus particle is, remains in the air and can be inhaled to infect someone else [5,6]. There is a high risk of contracting the virus through the air, so several countries have made wearing a mask when outdoors a must. Deaths and illnesses caused by COVID-19 have decreased as a result of the mask's widespread use. In addition, health care costs have been decreased, averting a complete breakdown of medical infrastructure [7]. Furthermore, mask use in conjunction with social isolation has helped to reduce the exponential growth rate of the disease's spread. In the first place, they serve to keep people from inhaling and spreading the aerosolized viruses they may have breathed in while talking, coughing,

sneezing, etc. The mask's material, on the other hand, can trap the flammable particles within its pores. In addition, wearing a mask has been quite useful in reducing the spread of the disease from asymptomatic individuals to the general public [8]. New research confirms that the use of surgical masks significantly cuts down on the release of infectious particles. While coronavirus was found in 30%-40% of samples taken from people wearing face masks, neither the droplets nor the aerosols were infectious for those who wore them. Results from a study using breathed air samples from individuals infected with SARS-CoV and MERS-CoV show that the use of surgical masks significantly decreases the release of virus particles [9]. When wearing a surgical mask, exhaled air should leave the nose and mouth at a high velocity and be directed frontally, as recommended by the Centers for Disease Control and Prevention (CDC) [10,11]. Particles are 3-8 microns thick (1 micron = 0.001 mm) and hit the interior of the mask at close range. Bacteria and other particles are contained even if air leaks out the sides, since they are too thick to follow the flow lines of the air that escapes from the edges if the seal is properly adjusted. For masks to be effective, wearers must follow all basic hygiene guidelines, with the most important being that the mask completely covers the face, including the mouth and nose. With an incomplete, improper, or asymmetric fit, the possibility of infection is greatly increased [12]. It is crucial to regulate the proper

application of masks because of their significance. As a result, the use of non-pharmaceutical products for controlling the spread of the virus has increased [13]. Due to the need for stricter regulation of masks in public or other venues frequented by a significant number of people, AI-based approaches have become increasingly important.

## 2.LITERATURE SURVEY

[1] C. Szegedy, S. Ioffe, V. Vanhoucke, and A. A. Alemi, "Inception-v4, inception-resnet and the impact of residual connections on learning," in *Thirty-first AAAI conference on artificial intelligence, 2017*.

The adoption of extremely deep convolutional networks has enabled the most significant advancements in picture identification performance in the last few years. The Inception concept has been proven to be highly efficient at a low computational cost. This year's ILSVRC competition found that the usage of residual connections, along with a more traditional architecture, led in equivalent performance to the Inception-v3 networks. Are there any advantages to combining Inception architectures with residual connections? Training Inception networks with residual connections, as we demonstrate in this research, greatly increases training speed. According to the study, Inception networks with residual connections appear to outperform similarly priced Inception networks by a small percentage as well. Additionally, we demonstrate a variety

of novel, more efficient Inception network topologies, both residual and non-residual, as an additional bonus. On the ILSVRC 2012 classification task, single-frame recognition is considerably improved. We go on to show that activation scaling stabilises the training of extremely large residual Inception networks. With an ensemble of three residual networks and one Inception-v4 network, we achieved a top-five error rate of 3.08 percent on the ImageNet classification (CLS) test set.

[2] A. Krizhevsky, I. Sutskever, and G. E. Hinton, "Image categorization with deep convolutional neural networks," in *Advances in neural information processing systems (ed) (in Russian)*.

Our convolutional neural network was trained to classify the 1.2 million high-quality images in the ImageNet LSVRC-2010 contest into 1000 separate classes. Our top-1 and top-5 error rates of 37.5% and 17.0%, respectively, show that this is a significant improvement over the preceding state-of-the-art. The neural network is comprised of five convolutional layers, some of which are followed by max-pooling layers, and three fully-connected layers with a final 1000-way softmax. To speed up training, we used non-saturating neurons and a GPU implementation of the convolution function. One of our new regularisation methods, called "dropout," proved to be particularly efficient at reducing overlays in the fully-connected layers. In the ILSVRC-2012 competition, a variant

of this model came in first place with a top-5 test error rate of 15.3%, beating out the second-best entry's 26.23%.

[3] **Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR), 2015, pp. 1–9. "Going deeper with convolutions."**

At ImageNet, we demonstrated a deep convolutional neural network architecture dubbed Inception that is capable of achieving the new state of the art in classification and detection (ILSVRC14). The most noticeable characteristic of this design is its ability to make the best use of available network bandwidth. We were able to increase the network's breadth and depth while keeping the same computational budget thanks to meticulous planning. Architectural decisions were influenced by Hebbian principles and multi-scale processing intuition in order to achieve the highest possible level of quality. We used a 22-layer deep network called GoogLeNet in our application for

### 3. PROPOSED WORK

A two-phase face masks detection model has been proposed the location terrific datasets had been reviewed to train our customized face masks detector. Finally, with the aid of the utilization of the help of the library of Keras and TensorFlow we will highlight how we have developed a face masks detector model ([github.com/chandrikadeb7/Face-Mask-Detection](https://github.com/chandrikadeb7/Face-Mask-Detection)). Moreover, a two-fold method is moreover utilized for detecting face masks in pix as properly

ILSVRC14 to evaluate the quality of classification and detection.

[4] **ArXiv preprint arXiv:1409.1556 (A. Zisserman and K. Simonyan, "Very deep convolutional networks for large-scale image recognition").**

We investigate how the depth of a convolutional network impacts the accuracy of the network in the setting of large-scale image recognition. A relatively small (3x3) convolution filter architecture was used to assess increasing network depth and discovered that extending the depth to 16-19 weight layers offered significant gains over prior-art settings. Based on these findings, our team took first and second place in the ImageNet Challenge 2014 classification and localization tracks, respectively. It is also possible to generalise the model to other datasets and obtain cutting-edge results on those datasets as well. Our best-performing ConvNet models have been made available to academics so that they can continue to investigate the use of deep visual representations in computer vision, as from real-time video streams. Following Fig. three highlights our proposed methodology of two part based totally definitely COVID-19 Face Mask Detector Model.


#### 3.1 Face Mask Detector Training Phase

It has been proposed that a two-phase face masks detection model be used to train our proprietary face masks detector. Our face mask detector model ([github.com/chandrikadeb7/Face-Mask-Detection](https://github.com/chandrikadeb7/Face-Mask-Detection)) has been constructed using the help of the Keras and

TensorFlow libraries. In addition, a two-step approach is used to recognise face masks in both still images and live video feeds. Following Fig. 3, we provide our suggested two-part COVID-19 Face Mask Detector Model technique.



**Fig. 3** Multiple stages and detailed phases for the development of a face mask detector model (images by the authors) **a** represent the training phase of face detection model whereas **b** shows how the apply procedure works in face detection model



**Fig. 4** Working procedure of customized fully connected layer of MobileNetV2 architecture

detection and then categorised primarily based on with\_mask and without\_mask. This exploration has used a deep learning device involving TensorFlow and Keras to routinely classify face masks carrying situations. To gain this goal, a fantastic tuned mechanism on MobileNetV2 [11] structure has been conducted. Several applications of machine/deep learning processes and photo processing libraries have been used in this lookup which include OpenCV, scikit-learn, matplotlib, numpy, and many greater to educate the masks detector. To set up a baseline mannequin that saves a sizable quantity of time, a three-step manner of fine-tuning has additionally


been performed to put together the MobilenetV2 architecture. As our mannequin is for binary classification (mask and without\_mask) problem, consequently we have used binary cross-entropy, decay agenda of a studying rate, and Adam optimizer to assemble our model. After the completion of the education phase, we evaluated the ensuing mannequin on the check set and generated a classification document for inspection. Finally, we serialized the face masks classification mannequin to the disk.

### 3.2 Face Mask Detector for Webcam/Video Stream

A two-fold procedure of detecting masks from a webcam or video flow is

additionally applied. In order to pick out faces in the webcam a pre-trained mannequin supplied through the OpenCV framework used to be employed. The pre-trained mannequin is primarily based on Single-Shot-

Multibox Detector (SSD) and makes use of the spine of a ResNet-10 Architecture. Following Fig. 5 indicates the step by using step working technique of face masks detection strategy from video data



**Fig 5:Face Mask Detection Workflow For Webcam Or Video Stream**

## 4.RESULTS AND DISCUSSION



**Fig 5:with out mask**



**Fig 6:with Mask**

Detecting face masks or without face mask in real-time from a video stream

## 5.CONCLUSION

This paper introduces a technique that employs laptop computer vision and the MobileNet V2 form factor to help

prevent the spread of the COVID-19 virus and to assist law enforcement by reducing the amount of time they must

spend physically monitoring people in containment zones and public areas where surveillance is pervasive. Therefore, when the lockout is relaxed and the computerised song of public areas except circumstance is relaxed, this recommended laptop will feature in an environmentally friendly manner in the current state of affairs. In this study, we have explored at length the topic of face masks designed to safeguard human health. Real-time responses might dramatically cut down on infractions, boosting public safety by stopping the spread of the coronavirus and freeing up resources for other safety measures. It has multiple possible uses, including in churches, malls, subways, and airports.

## REFERENCES

1. Nishiura, H.; Jung, S.M.; Linton, N.M.; Kinoshita, R.; Yang, Y.; Hayashi, K.; Kobayashi, T.; Yuan, B.; Akhmetzhanov, A.R. The extent of transmission of novel coronavirus in Wuhan, China, 2020. *J. Clin. Med.* 2020, 9, 330. [CrossRef] [PubMed]
2. Pedersen, S.F.; Ho, Y.C. SARS-CoV-2: A storm is raging. *J. Clin. Investig.* 2020, 130, 2202–2205. [CrossRef]
3. Dawson, P.; Rabold, E.M.; Laws, R.L.; Conners, E.E.; Gharpure, R.; Yin, S.; Buono, S.A.; Dasu, T.; Bhattacharyya, S.; Westergaard, R.P.; et al. Loss of taste and smell as distinguishing symptoms of coronavirus disease 2019. *Clin. Infect. Dis.* 2021, 72, 682–685. [CrossRef] [PubMed]
4. Hossain, M.M.; Tasnim, S.; Sultana, A.; Faizah, F.; Mazumder, H.; Zou, L.; McKyer, E.L.J.; Ahmed, H.U.; Ma, P. Epidemiology of mental health problems in COVID-19: A review. *F1000Research* 2020, 9. [CrossRef] [PubMed]
5. Brooks, J.T.; Butler, J.C. Effectiveness of mask wearing to control community spread of SARS-CoV-2. *JAMA* 2021, 325, 998–999. [CrossRef]
6. Wang, J.; Pan, L.; Tang, S.; Ji, J.S.; Shi, X. Mask use during COVID-19: A risk adjusted strategy. *Environ. Pollut.* 2020, 266, 115099. [CrossRef]
7. Joo, H.; Miller, G.F.; Sunshine, G.; Gakh, M.; Pike, J.; Havers, F.P.; Kim, L.; Weber, R.; Dugmeoglu, S.; Waston, C.; et al. Decline in COVID-19 hospitalization growth rates associated with statewide mask mandates—10 states, March–October 2020. *Morb. Mortal. Wkly. Rep.* 2021, 70, 212. [CrossRef]
8. Li, T.; Liu, Y.; Li, M.; Qian, X.; Dai, S.Y. Mask or no mask for COVID-19: A public health and market study. *PLoS ONE* 2020, 15, e0237691. [CrossRef]
9. Leung, N.H.; Chu, D.K.; Shiu, E.Y.; Chan, K.H.; McDevitt, J.J.; Hau, B.J.; Yen, H.-L.; Li, Y.; Ip, D.K.M.; Peiris, J.S.M.; et al. Respiratory virus shedding in exhaled breath and efficacy of face masks. *Nat. Med.* 2020, 26, 676–680. [CrossRef]
10. U.S. Food & Administration (FDA). N95 Respiradores Y Mascarillas Quirúrgicas (Mascarillas). Available online: <https://www.fda.gov/medical-devices/personal-protective-equipment-infection-control/n95-respirators-and-surgical->



- masks-face-masks (accessed on 11 March 2020).
11. Centers for Disease Control and Prevention. CDC 24/7. Frequently Asked Questions about Personal Protective Equipment. Available online: <https://www.cdc.gov/coronavirus/2019-ncov/hcp/respirator-use-faq.html> (accessed on 14 August 2021).
  12. SANDETEL Junta de Andalucía. Estado del Arte: E-Salud & E-Inclusión Estudio de Las Tecnologías de la Información y la Comunicación Aplicadas a la Salud y a la Inclusión; Dandatel: Seville, Spain, 2011.
  13. Aiello, A.E.; Perez, V.; Coulborn, R.M.; Davis, B.M.; Uddin, M.; Monto, A.S. Facemasks, Hand Hygiene, and Influenza among Young Adults: A Randomized Intervention Trial. *PLoS ONE* 2012, 7, e29744. [CrossRef]
  14. Chung, Y.; Chou, C.A.; Li, C.Y. Central Attention and a Dual Path Convolutional Neural Network in Real-World Tree Species Recognition. *Int. J. Environ. Res. Public Health* 2021, 18, 961. [CrossRef]
  15. Szegedy, C.; Vanhoucke, V.; Ioffe, S.; Shlens, J.; Wojna, Z. Rethinking the Inception Architecture for Computer Vision. In Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR), Las Vegas, NV, USA, 27–30 June 2016; pp. 2818–2826.
  16. Nieto-Rodríguez, A.; Mucientes, M.; Brea, V.M. System for medical mask detection in the operating room through facial attributes. In Proceedings of the Iberian Conference on Pattern Recognition and Image Analysis, Santiago de Compostela, Spain, 17–19 July 2015; Springer: Cham, Switzerland, 2015; pp. 138–145.
  17. Chen, Y.; Hu, M.; Hua, C.; Zhai, G.; Zhang, J.; Li, Q.; Yang, S.X. Face mask assistant: Detection of face mask service stage based on mobile phone. *IEEE Sens. J.* 2021, 21, 11084–11093. [CrossRef]
  18. Nagrath, P.; Jain, R.; Madan, A.; Arora, R.; Kataria, P.; Hemanth, J. SSDMNv2: A real time DNN-based face mask detection system using single shot multibox detector and MobileNetV2. *Sustain. Cities Soc.* 2021, 66, 102692. [CrossRef]
  19. Howard, A.G.; Zhu, M.; Chen, B.; Kalenichenko, D.; Wang, W.; Weyand, T.; Andreetto, M.; Adam, H. Mobilenets: Efficient convolutional neural networks for mobile vision applications. *arXiv Prepr.* 2017, arXiv:1704.04861.
  20. Mata, B.U. Face Mask Detection Using Convolutional Neural Network. *J. Nat. Remedies* 2021, 21, 14–19.
  21. Jauhari, A.; Anamisa, D.R.; Negara, Y.D.P. Detection system of facial patterns with masks in new normal based on the Viola Jones method. *J. Phys. Conf. Ser.* 2021, 1836, 012035. [CrossRef]