



International Journal for Innovative Engineering and Management Research

A Peer Reviewed Open Access International Journal

www.ijiemr.org

COPY RIGHT



ELSEVIER
SSRN

2020 IJEMR. Personal use of this material is permitted. Permission from IJEMR must be obtained for all other uses, in any current or future media, including reprinting/republishing this material for advertising or promotional purposes, creating new collective works, for resale or redistribution to servers or lists, or reuse of any copyrighted component of this work in other works. No Reprint should be done to this paper, all copy right is authenticated to Paper Authors

IJEMR Transactions, online available on 27th Sept 2020. Link

[:http://www.ijiemr.org/downloads.php?vol=Volume-09&issue=ISSUE-09](http://www.ijiemr.org/downloads.php?vol=Volume-09&issue=ISSUE-09)

Title: **PROBLEMS ENERGY SAVING ALTERNATING CURRENT MOTORS INAN ELECTRIC GENERATOR IN THE INDUSTRIAL COMPANIES**

Volume 09, Issue 09, Pages: 210-211

Paper Authors

Nazirjonova SH., Nasretdinova F.N.



USE THIS BARCODE TO ACCESS YOUR ONLINE PAPER

To Secure Your Paper As Per **UGC Guidelines** We Are Providing A Electronic Bar Code

PROBLEMS ENERGY SAVING ALTERNATING CURRENT MOTORS IN AN ELECTRIC GENERATOR IN THE INDUSTRIAL COMPANIES

Nazirjonova SH., Nasretdinova F.N.

Fergana Polytechnic Institute Yusupova D.A. Fergana State University

Annotation: This article is about ensuring the reliable operation of power generation equipment and obtaining quality electricity from it. Reducing reactive energy consumption provides energy savings. Electric motors play an important role in power generation. They need to be constantly monitored to ensure their reliability.

Key words: electric motor, alternating current, quality electric power, induction motor, minimum reactive power, different electric generator.

Introduction

Nowadays when it says that developed country we can understand firstly industry manufactures with high level. Electric motor plays significant role in a process of manufacturing in an industrial companies. So electric motors considers main component part of electric generator. As we know in manufacturing it is mainly used Alternating current motor which works through alternating current. At the present time by taking into consideration of different electric generator is included near 70% electric energy usage, it is required to put into practice of thrifty AC motors of energy. Working principle of AC motor is based on inserted current cable of magnetic field which are mutual influence with this field. It is appeared that main electric energy is extravagances in induction motors is the same with magnetic fields extravagances induction motors power extravagances.

Main part

Inductor motors power extravagances divide into active and reactive power extravagances. If it works for putting in motion of Motor's active power generator, reactive power generates

rotating magnetic current in a motor and with the help of this, current is moved active power with necessary amount from fire catcher to erector. In a low part, there are some methods of reducing Inductor motor's power extravagances:

- Changing from a full loaded motor to little loaded motor.
- Changing from fire catcher of motor's triangle scheme to star scheme.
- Decreasing idler working order of motors
- Limiting current of setting to work through reducing time of setting to work
- Increasing $\cos\phi$ value of power coefficient through equalizing of reactive power.

Controlling reactive power of consuming motor according to value of loading with the help of frequency modifier is new and efficiently method it will be cause to increase consuming motor's reactive power from system and to be less of nominal value from real loading moment of induction

motors as a result power coefficient of motor will become weak. Induction motor implements base of adapting minimum value of consumption of motor's reactive power as a result of erecting fire catchers power according to value of loading in the motor shaft For being minimum reactive power, it should be controlled through legality to loading moments value of fire catcher's power

$$y = \alpha \sqrt{\mu p}$$

Here : $y = U_{1f}/U_{2f}$ - relative value with respect nominal value of fire – catcher power according to the given frequency's value ; $\alpha = 1/2 \frac{U_{1f}}{U_{2f}}$ - relative value with respect nominal value of frequency μC – relative value of loading moment it would be taken as a criterion not increasing erector current's value which is showed as limited value of power erecting processes and as a result it changes frequency and consumes reactive power in a minimum value when it's loading moment of erecting velocity's inductor motor is in a different value.

References:

1. Jacobsson S., Johnson A. The diffusion of renewable energy technology: an analytical framework and key issues for research //Energy policy. – 2000. – T. 28. – №. 9. – C. 625-640
2. Grilli F. et al. Computation of losses in HTS under the action of varying magnetic fields and currents //IEEE Transactions on Applied Superconductivity. – 2013. – T. 24. – №. 1. – C. 78-110.
3. Morgan M. G. Power frequency electric and magnetic fields: Issues of risk management and risk communication //Biologic Effects of Electric and

Magnetic Fields. – 2014. – T. 2. – C. 297-319

4.

https://www.faulhaber.com/fileadmin/user_upload_global/support/MC_Support/Drive_Electronics/AppNotes/Faulhaber_AN178_EN.pdf