



International Journal for Innovative Engineering and Management Research

A Peer Reviewed Open Access International Journal

www.ijiemr.org

COPY RIGHT



ELSEVIER
SSRN

2021IJIEMR. Personal use of this material is permitted. Permission from IJIEMR must be obtained for all other uses, in any current or future media, including reprinting/republishing this material for advertising or promotional purposes, creating new collective works, for resale or redistribution to servers or lists, or reuse of any copyrighted component of this work in other works. No Reprint should be done to this paper, all copy right is authenticated to Paper Authors

IJIEMR Transactions, online available on 29th Jun 2021. Link

[:http://www.ijiemr.org/downloads.php?vol=Volume-10/ISSUE-06](http://www.ijiemr.org/downloads.php?vol=Volume-10/ISSUE-06)

DOI: 10.48047/IJIEMR/V10/I06/49

Title **STUDY OF THE MOVEMENT OF PUBESCENT SEEDS IN THE FLOW OF AN AQUEOUS SOLUTION OF MINERAL FERTILIZERS**

Volume 10, Issue 06, Pages: 247-252

Paper Authors

MamadaliievAdxamjonTuxtamirzaevich, son of BakhtiyorMaqsud, UmarovIsroil



USE THIS BARCODE TO ACCESS YOUR ONLINE PAPER

To Secure Your Paper As Per **UGC Guidelines** We Are Providing A Electronic Bar Code

UDC633.511:631.543.2

STUDY OF THE MOVEMENT OF PUBESCENT SEEDS IN THE FLOW OF AN AQUEOUS SOLUTION OF MINERAL FERTILIZERS

Mamadaliyev Adxamjon Tuxtamirzaevich, son of Bakhtiyor Maqsud,
Umarov Isroil

PhD, docent, Department of technology of production of building materials products and structures, Faculty of construction technology, Namangan engineering construction institute, Namangan, Uzbekistan, e-mail: Mamadaliyev6300@gmail.com, phone: +99897-253-63-00

Abstract.

This article presents the results of research on the theoretical substantiation of the behavior of hairy seeds soaked in an aqueous solution of mineral fertilizers and micronutrient compositions after falling from the spreader.

Keywords: pubescent cotton seeds, flowability, enveloping, pelleting, protective and nutritious shell, devices, bowl-shaped drum, suspension, water, mineral fertilizer.

Introduction

In recent years, important decisions and many measures have been taken in the country to radically improve the seed industry, increase the production of quality and competitive products. Particular attention is paid to the development of resource-saving technologies and techniques in the preparation of seeds for sowing, sorting and chemical treatment of agricultural crops.

With this in mind, we offer a device that ensures the coating of hairy seeds in a continuous technological process with an aqueous solution of mineral fertilizers and trace elements.

Methods.


The essence of this technology is that the seeds are first sorted in an electric field on all their physical and mechanical properties. The sorted hairy seeds are delivered to the vertical cylinder at a certain rate and spread in conical spreaders, soaked in a mixture of water and mineral fertilizers, then collected in truncated cone-shaped

collectors and dropped into a hemispherical shell drum rotating at a certain speed around a vertical axis.

Results

The hairy seeds move in a stream of a mixture of mineral fertilizers with water sprinkled by the shelling device after the velocity has dropped from the conical spreader [1,2,3,4,5].

Seeds moving in the aqueous solution of macro- and micronutrient compositions are affected by the driving force $R_x = km(V_0 - \dot{x})$ of the flow along the X axis and the resistance force $R_z = km \dot{z}$ along the Z axis and the gravitational force $G = mg$ (Fig. 1).



1 – conical spreader; 2 – sprayer

Figure 1. Scheme for studying the movement of hairy seeds in the flow of aqueous solution of macro and micronutrient compositions

Taking into account these forces, we construct the differential equation of the motion of the hairy seeds along the X and Z axes.

$$m\ddot{x} = km(V_0 - \dot{x}) \quad (1)$$

and

$$m\ddot{z} = -km\dot{z} + mg \quad (2)$$

or

$$\ddot{x} = k(V_0 - \dot{x}) \quad (3)$$

and

$$\ddot{z} = -k\dot{z} + g, \quad (4)$$

where k - is a proportional coefficient of constant magnitude;

V_0 - is the flow rate of the mixture of water and mineral fertilizers, m /s.

m - seed mass, kg.

g - is the acceleration of free fall, m / s²

We integrate equations (3) and (4). To do this, we replace \ddot{x} (dx/dt) in equation (3) and write it in the following form

$$\frac{d\dot{x}}{V_0 - \dot{x}} = k dt. \quad (5)$$

Integrating equation (5), we obtain the following result

$$-\ln[V_0 - \dot{x}] = kt + C_1, \quad (6)$$

where C_1 - is the integration constant

According to the scheme in figure 1, it occurs when $t = 0$, $\dot{x} = V_A \sin \alpha$ will be. \dot{x} expressing this value of (6), $C_1 = -\ln(V_0 - V_A \sin \alpha)$ we find that C_1 by putting this value of in equation (6)

$$-\ln[V_0 - \dot{x}] = kt - \ln(V_0 - V_A \sin \alpha) \quad (7)$$

or

$$kt = \ln \frac{V_0 - V_A \sin \alpha}{V_0 - \dot{x}} \quad (8)$$

we get the equation.

We find \dot{x} from equation (8)

$$\dot{x} = V_0 - (V_0 - V_A \sin \alpha) e^{-kt} \quad (9)$$

By substituting \dot{x} (dx/dt) for, we obtain the following equation

$$dx = V_0 dt - (V_0 - V_A \sin \alpha) e^{-kt} dt \quad (10)$$

Integrating this equation, we obtain the following result

$$x = V_0 t + \frac{(V_0 - V_A \sin \alpha)}{k} e^{-kt} + C_2 \quad (11)$$

According to the scheme in figure 1, at $t = 0$, $x = 0$. If we put these values in (11), $C_2 = -(V_0 - V_A \sin \alpha)/k$ it follows that. With this in mind, we bring equation (11) to the following form

$$x = V_0 t - \frac{(V_0 - V_A \sin \alpha)}{k} (1 - e^{-kt}) \quad (12)$$

Now we move on to the integration of equation (4). $\ddot{z} = (d\dot{z}/dt)$ given that, we write equation (4) in the following form

$$\frac{d\dot{z}}{g - k\dot{z}} = dt \quad (13)$$

Integrating equation (13) once, we obtain the following expression

$$-\frac{1}{k} \ln(g - k\dot{z}) = t + C_3 \quad (14)$$

When $t = 0$, $\dot{z} = V_A \cos \alpha$. Putting these values of t and \dot{z} in the expression (14),

$C_3 = -\frac{1}{k} \ln(g - kV_A \cos \alpha)$ we get the result. C_3 substituting this value of (14) into the expression, we obtain the following final result

$$\ln \frac{g - kV_A \cos \alpha}{g - k\dot{z}} = kt \quad (15)$$

from the last expression

$$\dot{z} = \frac{g}{k} - \frac{g - kV_A \cos \alpha}{k} e^{-kt} \quad (16)$$

arises.

$\dot{z} = (dz/dt)$ using equation, we write equation (16) as follows

$$dz = \frac{g}{k} dt - \frac{g - kV_A \cos \alpha}{k} e^{-kt} dt \quad (17)$$

Integrating equation (17), we obtain the following

$$z = \frac{g}{k} t + \frac{g - kV_A \cos \alpha}{k^2} e^{-kt} + C_4 \quad (18)$$

According to the scheme in figure 1, $z = 0$ at $t = 0$. If we express these values

in (18), $C_4 = -(g - kV_A \sin \alpha) / k^2$ it turns out that.

With this value of the integration constant C_4 , expression (18) looks as follows

$$z = \frac{g}{k}t - \frac{g - kV_A \cos \alpha}{k^2}(1 - e^{-kt}). \quad (19)$$

The following expression was obtained to determine the velocity V_A of hairy seeds falling from the distributor of the peeling device.

$$V_A = \sqrt{(V_T \cos \alpha)^2 + 2g \left(\frac{0,5D}{\sin \alpha} - l_T \right) (\cos \alpha - f_1 \sin \alpha)} \quad (20)$$

Taking into account expression (20), the equations of motion in an aqueous solution of mineral fertilizers and micronutrient compositions of hairy seeds are as follows:

$$X = V_0 t - \frac{1}{k} \left\{ V_0 - \sqrt{(V_T \cos \alpha)^2 + 2g \left(\frac{0,5D}{\sin \alpha} - l_T \right) (\cos \alpha - f_2 \sin \alpha)} \right\} \sin \alpha (1 - e^{-kt});$$

$$Z = \frac{g}{k}t - \frac{1}{k^2} \left\{ g + k \sqrt{(V_T \cos \alpha)^2 + 2g \left(\frac{0,5D}{\sin \alpha} - l_T \right) (\cos \alpha - f_1 \sin \alpha)} \right\} \sin \alpha (1 - e^{-kt}).$$

Discussions.

Based on the analysis of the obtained expressions (21) and (22), it can be argued that the quality and amount of adhesion in an aqueous solution of mineral fertilizers to the surface of the pubescent cotton seeds depends on the time t of their interaction with the solution flow, the solution velocity V_0 , the diffuser diameter D , the angle taper α , velocity V_t and place l_T of pubescent seeds getting to it.

By changing these factors, it is possible to achieve the quality and quantity

of adhesion of the solution to the surface of the pubescent seeds.

After leaving the flow of an aqueous solution of mineral fertilizers, the pubescent seeds V_{xz} at a rate

$$V_{xz} = \sqrt{(\dot{x})^2 + (\dot{z})^2} = \sqrt{\left[V_0 - \frac{(V_0 - V_A \sin \alpha) e^{-kt}}{k} \right]^2 + \left[\frac{g}{k} - \frac{g - kV_A \cos \alpha}{k} e^{-kt} \right]^2} \quad (23)$$

fall on the truncated cone-shaped collector and, being collected in its lower part, fall on the working surface of the second cone-shaped diffuser and the technological process is repeated [6,7,8,9,10]. In order for the pubescent seeds that have fallen into the truncated cone-shaped collector to move along its working surface and collect in its lower part, the following condition must be met

$$\beta < 90^\circ - \varphi_2, \quad (24)$$

where β is the angle of inclination of the generatrix of the cone-shaped collector relative to the vertical plane, degree; φ_2 - angle of friction of pubescent seeds sprayed with an aqueous solution of mineral fertilizers on the working surface of a truncated cone-shaped collector, degree.

Conclusion

Based on the results of experimental studies, we assume that the maximum value of φ_2 is 60° , and we express this value (24) to ensure that the pubescent seeds, coated with an aqueous solution of mineral fertilizers and a composition of trace elements, that the coal of the setting of the forming cone-shaped collector should not be more than 30° from the vertical plane.

REFERENCES

1. Gafurov K., Rosaboev A., Mamadaliev A. Pelleting of dropped cotton seeds with mineral fertilizer // Scientific and technical journal of FarPI. - Fergana, 2007. - № 3. - B. 55-59.
2. Mamadaliyev Adhamjon Tuxtamirzayevich. Study of pubescent seeds moving in a stream of water and mineral fertilizers. International journal on Integrated Edukation. Volume 3, Issue 12, December 2020 / 489.
3. RUz patent No. IAP 03493. Method of covering the surface of agricultural crops seeds with a protective and nutritious shell and devices for its implementation / K. Gafurov, A. Khozhiev, AT Rosaboev, AT Mamadaliev // BI. - 2007. - No. 11
4. Rosaboev A., Mamadaliev A. Presowing treatment of pubescent cotton seeds with a protective and nutritious shell, consisting of a composition of macro- and micro fertilizers // Theoretical and practical issues of the development of scientific thought in the modern world: Collection of articles. UFA RITS. Bashkir State University, 2013. - pp. 174-176. (In Russian).
5. Rosaboev A.T., Mamadaliev A.T., Tukhtamirzaev A.A. Theoretical substantiation of the movement of lowered cotton seeds after entering from the distributor in the process of encapsulation // Materials of International Scientific and Practical Conferences Society of Science and Creativity. - Kazan, 2017. - No. 5. - S. 239-245. (In Russian).
6. Rosaboev A.T., Mamadaliev A.T., Tukhtamirzaev A.A. Theoretical substantiation of the parameters of the encapsulating drum of pubescent seeds // Materials of International Scientific and Practical Conferences Society of Science and Creativity. - Kazan, 2017. - No. 5. - S. 246-249. (In Russian).
7. Gafurov K., Mamadaliev A. Technology and devices of shelling of seeds with macro- and micro-fertilizer compositions. // Journal of Scientific and Technical Cotton and Grain 2002 №2 - S. 17-21
8. Rosaboev A., Mamadaliev A. Theoretical substantiation of parameters of the cup-shaped coating drums. IJARSET. ISSN:2350-0328. International journal of Advanced Research in Science, Engineering and Technology. Volume 6, Issue 11, November 2019 s11779-11783
9. Tokhtakoziev A., Rosaboev A., Mamadaliev A., Imamkulov U. Substantiation of the parameters of the conical spreader of the device for coating hairy seeds with mineral fertilizers. // Scientific and technical journal of FarPI. - Fergana, 2014. - № 2. - S. 46-49.
10. Tokhtakoziev A., Rosaboev A., Mamadaliev A. Theoretical substantiation of parameters of a drum of shelling of hairy seeds. // Scientific and technical journal of FarPI. - Fergana, 2012. - № 2. - P.34-36.
11. Arifjanov A.M., Akmalov Sh. Akhmedov I., Ataqulov D. [Evaluation of deformation procedure in waterbed of rivers. XII International Scientific Conference on Agricultural Machinery Industry. IOP Conf. Series: Earth and Environmental Science 403 \(2019\) 012155](#)
<https://www.scopus.com/authid/detail.uri?authorId=57214102503>
12. Arifjanov A. M., Akhmedov I. G., Ibragimova Z. Analysis Of Natural Field Research In The Assessment Of Processes In The Foothills // The American Journal of Applied sciences. - 2020. - T. 2. - №. 09. - C. 293-298.



13. Akhmedov I.G'., Muxitdinov M., Umarov I., Ibragimova Z. Assessment of the effect of sedibles from sokhsoy river to kokand hydroelectric power station //InterConf. – 2020.

14. Arifjanov A., Samiyev L., Akhmedov I., Ataqulov D. Innovative Technologies In The Assessment Of Accumulation And Erosion Processes In The Channels //Turkish Journal of Computer and Mathematics Education (TURCOMAT). – 2021. – T. 12. – №. 4. – C. 110-114